


MK286-32H-8S4P-24V-10W-L280W20-20730

Built-in PCB lighting modules

The new MK286-32H-20730 is characterised by its particularly easy-to-use mounting and connection options (ZHAGA-compliant hole spacing). Thanks to producing a homogeneous light field without any discernible individual light points, these LED modules are ideal for use with reflectors in luminaires constructed for T5 and T8 lamps.



Technical data

Dimensions: 280x 20 mm
 On-board push-in terminals (WAGO 2059)
 Allowed operating temperature at tc point:
 -40 to 85 °C (> 450 mA)
 -40 to 105 °C (450 mA)
 Use of external LED constant-current drivers
 Efficiency up to 199 lm/W
 Colour rendering index Ra: > 80
 Colour accuracy initially: 3 SDCM;
 after 70,000 hrs. operating time: 4 SDCM
 Lumen maintenance L80/B10:
 70,000 hrs. (lf450 mA)



Specific technical data


Type	Typ. luminous flux at tp = 25 °C	Typ. luminous flux at tp = 65 °C	Typ. Colour temperature (CCT)	Colour rendering index CRI	Min. forward voltage at tp = 65 °C	Max. forward voltage at tp = 25 °C	Typ. forward current	Typ. power consumption at tp = 65 °C	Max. forward current	Efficacy of the module at tp = 25 °C	Efficacy of the module at tp = 65 °C
------	----------------------------------	----------------------------------	-------------------------------	----------------------------	------------------------------------	------------------------------------	----------------------	--------------------------------------	----------------------	--------------------------------------	--------------------------------------

Linear-Z LED-module – L280 W20 H8

10W-20730LN	1,990Lm	1,920Lm	4,000K	>80	21.6V	24.8V	450mA	10.1W	640mA	199Lm/W	192Lm/W
	1,563Lm	1,509Lm					350mA	7.7W		203Lm/W	196Lm/W
	1,123Lm	1,085Lm					250mA	5.4W		208Lm/W	201Lm/W
10W-20730RK	1,780Lm	1,710Lm	4,000K	>80	21.6V	24.8V	450mA	10.1W	640mA	178Lm/W	171Lm/W
	1,427Lm	1,373Lm					350mA	7.8W		183Lm/W	176Lm/W
	1,034Lm	996Lm					250mA	5.5W		188Lm/W	181Lm/W

Emission data at tp = 65 °C | * Colour tolerance: 3 MacAdam | ** Production tolerance of luminous flux and efficiency: ±10 % | Min. CRI Ra: > 80

DIMENSIONS (All dimensions in mm)



Typical applications

- Installation in luminaires comerciales
- Office lighting
- Retail, corridor and shelf lighting
- T5/T8 replacement as built-in module
- Furniture lighting
- Backlighting for advertising

Website

<http://www.led-module.cn/pro118>

